



Clarity 21.5" ED Open Frame Display

The Clarity Touch and Display range has been developed to provide manufacturers with maximum product flexibility combined with minimum integration cost.

The range features a standard frame design that can be upgraded to incorporate:

- MicroTouch Single-Touch SCT
- MicroTouch Multi-Touch PCAP System
- Projective Glass (SCT / PCAP Options)
- ThruTouch

The rugged metal frame provides integration points on all 4 back sides and a VESA mount to the back. The screens come equipped with industrial electronics and TFT panels for maximum reliability and performance. The AD board supports standard 3 point connection for VGA/ DVI and DP (Display port) and offers standard 12 volt operation.



CLARITY

Features	Technical Spec – Display only
<ul style="list-style-type: none"> • Wide Viewing Angle Display • VGA / DVI / DP Signal input • USB B Touch Output • 100mm VESA Mount to Back • Mounting Points all 4 Sides • Option for Touch • Standard 12 Volt Operation 	<ul style="list-style-type: none"> • Resolution 1920 x 1080 • Inputs VGA / DVI / DP (1.2) • Operating Temperature 0°C to 50 °C • Luminance 250cd/m² • Contrast Ratio 1000:1 • Active Display Area 476.06 (W) x 267.79 (H) • Outer Dimensions 498 (W) x 295.55 (H) x 53.4 (D)

Description	Part No.	Accessories	Part No.
21.5" ED Open Frame Display	31161010	VGA Cable 1.8m	31123929
21.5" ED + MicroTouch Single-Touch SCT System	31161011	DVI Cable 1.8M	31123920
21.5" ED + SCT Style Protective Glass	31161012	DP Cable 1.5m	31123943
21.5" ED + MicroTouch Multi-Touch PCAP System	31161013	USB Cable A/B 1.8m	31130143
21.5" ED + PCT Protective Glass	31161014	PSU 12v 3.5 amp	33145342
21.5" ED + ThruTouch	31161076	UK Power Cord 1.8m	13021102
		EU Power Cord 1.8m	33145324