

Clarity 23.8" ED Open Frame Display

The Clarity Touch and Display range has been developed to provide manufacturers with maximum product flexibility combined with minimum integration cost.

The range features a standard frame design that can be upgraded to incorporate:

- **MicroTouch Single-Touch SCT System**
- **MicroTouch Multi-Touch PCAP System**
- **ThruTouch**
- **MicroTouch Protective Glass (SCT / PCAP Options)**

The rugged metal frame provides integration points on all 4 back sides and a VESA mount to the back. The screens come equipped with industrial electronics and TFT panels for maximum reliability and performance. The AD board supports standard 3 point connection for VGA/ DVI and DP (Display port) and offers standard 12 volt operation.



Features

- Wide Viewing Angle Display
- VGA / DVI / DP Signal input
- USB B Touch Output
- 100mm VESA Mount to Back
- Mounting Points all 4 Sides
- Option on for Touch
- Standard 12 Volt Operation

Technical Spec – Display only

- Resolution 1920 x 1080
- Inputs VGA / DVI / DP (1.2)
- Operating Temperature 0°c to 50 °c
- Luminance 250cd/m²
- Contrast Ratio 1000:1
- Active Display Area 527.04 (W) x 296.46 (H)
- Outer Dimensions 545.4 (W) x 323.9 (H) x 49.2 (D)

Description	Part No.	Accessories	Part No.
23.8" ED Open Frame Display	31161022	VGA Cable 1.8m	31123929
23.8" ED + MicroTouch Single-Touch SCT System	31161023	DVI Cable 1.8M	31123920
23.8" ED + SCT Style Protective Glass	31161024	DP Cable 1.5m	31123943
23.8" ED + MicroTouch Multi-Touch PCAP System	31161025	USB Cable A/B 1.8m	31130143
23.8" ED + PCT Protective Glass	31161026	PSU 12v 3.5 amp	33145342
23.8" ED + ThruTouch	31161044	UK Power Cord 1.8m	13021102
		EU Power Cord 1.8m	33145324