

Clarity 27" ED Open Frame Display

The Clarity Touch and Display range has been developed to provide manufacturers with maximum product flexibility combined with minimum integration cost.

The range features a standard frame design that can be upgraded to incorporate:

- **MicroTouch Multi-Touch PCAP System**
- **MicroTouch Glass**

The rugged metal frame provides integration points on all 4 back sides and a VESA mount to the back. The screens come equipped with industrial electronics and TFT panels for maximum reliability and performance. The AD board supports standard 3 point connection for VGA/ DVI and DP (Display port) and offers standard 12 volt operation.



Features

- Wide Viewing Angle Display
- VGA / DVI / DP Signal input
- USB B Touch Output
- Mounting Points to back of frame
- Option for Touch/Protective Glass
- Standard 12 Volt Operation

Technical Spec – Display only

- Resolution 1920 x 1080
- Inputs VGA / DVI / DP (1.2)
- Operating Temperature 0°c to 50 °c
- Luminance 300cd/m²
- Contrast Ratio 3000:1
- Active Display Area 597.06 (W) x 336.15 (H)
- Outer Dimensions 633 (W) x 363.6 (H) x 41.8 (D)

| Description | Part No. | Accessories | Part No. |
|------------------------------------|--------------------------|--------------------|--------------------------|
| 27" ED AUO Open Frame Display | 31161096 | VGA Cable 1.8m | 31123929 |
| 27" ED AUO + MicroTouch PCAP Touch | 31161097 | DVI Cable 1.8m | 31123920 |
| 27" ED AUO + MicroTouch Glass | 31161098 | DP Cable 1.5m | 31123943 |
| | | USB Cable A/B 1.8m | 31130143 |
| | | PSU 12v 3.5 amp | 33145342 |
| | | UK Power Cord 1.8m | 13021102 |
| | | EU Power Cord 1.8m | 33145324 |