



Clarity 32" ED Open Frame Display

The Clarity Touch and Display range has been developed to provide manufacturers with maximum product flexibility combined with minimum integration cost.

The range features a standard frame design that can be upgraded to incorporate:

- **Microtouch Multi-Touch PCAP System**
- **Microtouch Protective Glass**

The rugged metal frame provides integration points to the back of the rugged metal frame. The screens come equipped with industrial electronics and BOE TFT panels for maximum reliability and performance. The AD board supports standard 3 point connection for VGA/ DVI and DP (Display port) and offers standard 24 volt operation.



Features

- Wide Viewing Angle Display
- VGA / DVI / DP Signal input
- USB B Touch Output
- Mounting Points to back of frame
- Option for Touch/Protective Glass
- Standard 24 Volt Operation

Technical Spec – Display only

- Resolution 1920 x 1080
- Operating Temperature 0°c to 50 °c
- Luminance 400cd/m²
- Contrast Ratio 1200:1
- Active Display Area 698.4 (W) x 392.85 (H)

Description	Part No.	Accessories	Part No.
32" ED AUO Open Frame Display	31161004	VGA Cable 1.8m	31123929
32" ED AUO + MicroTouch PCAP Touch	31161005	DVI Cable 1.8M	31123920
32" ED BOE + Protective Glass	31161006	DP Cable 1.5m	31123943
		USB Cable A/B 1.8m	31130143
		PSU 12v 3.5 amp	33145346
		UK Power Cord 1.8m	13021102
		EU Power Cord 1.8m	33145324