

## 40+ LUBRICANT – Kontakt 40 +E10



The solution to many problems in workshop and factory.

KONTAKT 40's special chemical composition makes it a reliable penetrating oil, lubricant, water displacer and corrosion protector. It forms a durable barrier against water and oxygen with its virtually invisible film of oil. The excellent spreading power guarantees an even and complete coverage of all parts.

### Application

- Electrical parts (plugs, switches, coils, leads, relays)
- Mechanical parts (tools, locks, hinges, nuts and bolts, fixtures, screws)
- Machinery
- Leisure (DIY , garden, home)
- Loosening corroded screws and other fasteners

### How to use

- Easy application by spraying.
- Provides drying and corrosion protection.
- Switch off devices before spraying.
- Suitable for cleaning and protecting various surfaces.

Part #: 28200157

### Key Features

Prevents electrical and electronic malfunction caused by water penetration, humidity, condensation or corrosion.

Cleans, lubricates, penetrates and loosens corrosion

Restores low contact resistance and stops leakage currents produced by humidity.

Prevents corrosion by displacing moisture.

Convenient 360° spray valve, can be used in all positions.

### Product Data

#### As delivered

- Density at 20°C Aerosol
- Bulk
- Colour
- Flash point (ASTM D 56)
- Viscosity at 20°C (ASTM D 2983)
- Coverage Aerosol
- Bulk

0,82 g/cm<sup>3</sup>  
0,83 g/cm<sup>3</sup>  
yellowish, transparent,  
78°C  
± 3 mPa.s  
7m<sup>2</sup>/200 ml Aerosol  
100 m<sup>2</sup>/l

#### Properties after drying off solvent

- Colour
- Flash point ASTM D 56)
- Ignition temperature (DIN 51794)
- Heat resistance
- Short-term heat resistance
- Typical film thickness
- Viscosity at 20°C ASTM D 2983

Colourless  
175°C  
250°C  
< 120°C  
150°C  
2µm  
64 mPa.s

